



PT. FUSI LIBERTI INFOSINDO

We Design and Support Electrical, Communication & IT Components

www.fulindo.co.id

Spesifikasi Modem GSM/GPRS MLiS MLL-S-37-DC

Items	Deskripsi	MLL-S-37-DC
1) Data Umum	Tipe Modem	MLL-S-37-DC
	Chipset untuk wireless module	Cinterion MC37i
2) Data Teknis	Range Frekuensi	Dual Band GSM 900/1800 MHz
	Sumber daya	9 - 30 Volt DC
	Konsumsi daya	Sleep mode: typ. 13mA Idle mode: typ. 25mA GPRS class 10 (average) 460 mA
	Temperatur Operasi	Normal : -20°C to +70°C
	Dimensi	Dimensions: 75mm x 65mm x 21mm Weight: 80 g Chassis Material: Alumunium
	AT command	Standard Hayes 3GPP
	Standards interface	<ul style="list-style-type: none">• Antena: SMA 50 Ohm (female)• RS232 sub - D9 female (EIA/TIA-232-F standards)• Manual Reset• Status LED
3) Sistem Komunikasi	Komunikasi data CSD (GSM)	<ul style="list-style-type: none">• Up to 14.4 kbps• V.110• Non-transparent mode• USSD support
	SMS	<ul style="list-style-type: none">• Point-to-point MO and MT• SMS cell broadcast• Text and PDU mode
	Komunikasi data GPRS - Kecepatan	GPRS class 10 dengan spesifikasi : Download : max 85.6 kbps Upload : max 42.8 kbps
	- Kelas mobile	Mobile station kelas B
	Komunikasi Fax	<ul style="list-style-type: none">• Fax group 3: Class 1, Class 2
4) Approval	International	R&TTE, FCC, CE0984
	Lokal (Indonesia)	Dirjen Postel Depkominfo 14553/POSTEL/2010 PLG ID : 1473